

EnduraTech Butyl Seam Tape

DESCRIPTION:

EnduraTech Butyl Seam Tape seals out air and moisture in homes, sunrooms, rooftops, basements, recreational vehicles, and more. Compared with asphalt tapes, EnduraTech Butyl Seam Tape can be applied in a wider temperature range and has higher peel strength. The modified butyl adhesive/sealant self-seals around fasteners and will not melt or stain like asphalt-based flashing tapes. Installation is cleaner, more watertight, and will last longer. EnduraTech Butyl Seam Tape is available in the following configuration:

CONFIGURATION:

- CR Coating Ready — 10 mils fabric, 20 mils butyl adhesive / sealant

TECHNICAL DATA:

Properties	Typical Value
Sealant Material	Modified Butyl
Peel Strength	17 lbs per linear inch
Tensile Strength	Butyl – 445 psi (with 60% elongation)
Water Resistance	Excellent – surface must be clean and dry before
Bonding Time	Immediate, watertight aggressive grip, full bond within 24 hrs
Application Temperature	32°F to 110°F 15°F to 35°F with spray adhesion promoter
Operating Limits	-40°F to 220°F
UV Resistance TPO & PE	Excellent
Shelf Life	18 – 24 months (adhesive)

PRECAUTIONS: Surfaces must be clean and free of moisture, and contamination. Do not stretch during application. Press down firmly starting at center and working toward outside edge of tape, removing bubbles. Keep away from children. All materials warranted to be standard commercial quality.

The information on our data sheets is to assist customers in determining whether our products are suitable for their applications. The customers must satisfy themselves as to the suitability for specific cases. NCFI Polyurethanes warrants only that the material shall meet its specifications; this warranty is in lieu of all other written or unwritten, expressed or implied warranties and NCFI Polyurethanes expressly disclaims any warranty of merchantability, fitness for a particular purpose, or freedom from patent infringement. Accordingly, buyer assumes all risks whatsoever as to the use of the material. Buyer's exclusive remedy as to any breach of warranty, negligence or other claim shall be limited to the purchase price of the material. Failure to adhere strictly to any recommended procedures shall relieve NCFI Polyurethanes of all liability with respect to the material or the use thereof.