

Dalton, GA

Hickory, NC

Mount Airy, NC

Salt Lake City, UT

Section 1: Identification

Product Identifier

Trade Name: R-72-005 Tan
Chemical Name: Urethane Coating
Recommended Use: Roof Coating
Restrictions on Use: For Industrial Use Only

Chemical Manufacturer Information

Name: NCFI Polyurethanes
Address: 1515 Carter St Mount Airy, NC 27030
Website: www.NCFI.com


Phone: (800) 346-8229
Fax: (336) 789-9586
Emergency Phone: CHEMTREC: 800-424-9300

Section 2: Hazard Identification

Classification of the substance or mixture:

| | |
|---|---|
| <ul style="list-style-type: none"> Respiratory Sensitisation Category 1A Skin Sensitisation Category 1 | <ul style="list-style-type: none"> Carcinogenicity Category 2 Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 1 |
| <ul style="list-style-type: none"> Corrosion/Irritation Category 2 Serious Eye Damage/Eye Irritation Category 1 | <ul style="list-style-type: none"> Flammable Liquid Category 3 Acute Toxicity - Inhalation Vapour Category 3 |

GHS Labeling:

| | |
|---|--|
|  | |
|---|--|

Hazard Statements:

| | |
|--|---|
| <ul style="list-style-type: none"> Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. Toxic if inhaled. | <ul style="list-style-type: none"> May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure |
|--|---|



SAFETY DATA SHEET According to GHS

PO Box 1528 • Mount Airy, NC 27030-1528
800.346.8229 • Fax 336.789.9586 • www.NCFI.com

Dalton, GA

Hickory, NC

Mount Airy, NC

Salt Lake City, UT

| Precautionary Statements: | |
|--|--|
| <ul style="list-style-type: none"> Do not breathe fume/gas/mist/vapors/spray | <ul style="list-style-type: none"> Wear protective gloves/eye protection/face protection |
| <ul style="list-style-type: none"> Keep away from heat, sparks, open flames and hot surfaces. | <ul style="list-style-type: none"> Ground container and receiving equipment. |
| <ul style="list-style-type: none"> No Smoking | <ul style="list-style-type: none"> Use explosion-proof electrical, ventilating, and lighting equipment |
| <ul style="list-style-type: none"> Take precautionary measures against static discharge | <ul style="list-style-type: none"> Use only non-sparking tools. |
| <ul style="list-style-type: none"> IF IN EYES: Rinse immediately with water for at least 15 minutes. Get medical attention immediately. | <ul style="list-style-type: none"> IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, have a trained individual administer oxygen. |
| <ul style="list-style-type: none"> IF ON SKIN: Wash with plenty of soap and water. | <ul style="list-style-type: none"> IF INGESTED: Harmful if swallowed. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. Immediately call a POISON CENTER or physician. |

Disposal: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Long-term (Chronic) Health Effects:

Carcinogenicity: Cancer hazard: Contains Crystalline Silica which can cause cancer. Risk of cancer depends on duration and level of exposure to dust generated from sanding surfaces or spray mists.
Contains Titanium Dioxide which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence with respect to humans and sufficient evidence in experimental animals.

Inhalation: Overexposure may cause lung damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and central nervous system damage.

Skin Contact: Prolonged contact may cause an allergic skin reaction.

Section 3: Composition

Hazardous Components

Type of product: Mixture

| <u>CAS#</u> | <u>Weight %</u> | <u>Name</u> |
|-------------|-----------------|-----------------------------|
| 9057-91-4 | 10 – 30 | Polyisocyanate Resin |
| 8052-41-3 | 5 - 10 | Stoddard solvent |
| 13463-67-7 | 3 - 7 | Titanium dioxide |
| 124-17-4 | 3 - 7 | Butyl carbitol acetate |
| 14808-60-7 | 3 - 7 | Quartz (Silica-Crystalline) |
| 140921-24-0 | 3 - 7 | Oxazolidine Hardener |
| 112945-52-5 | 1 – 5 | Fumed silica |
| 5989-27-5 | 0.5 - 1.5 | (d)-Limonene |
| 26471-62-5 | 0.1 - 1 | Toluene diisocyanate |

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.



SAFETY DATA SHEET According to GHS

PO Box 1528 • Mount Airy, NC 27030-1528
800.346.8229 • Fax 336.789.9586 • www.NCFI.com

Dalton, GA

Hickory, NC

Mount Airy, NC

Salt Lake City, UT

Section 4: First Aid Measures

| | |
|--|---|
| Inhalation: | Move to fresh air if symptoms develop. If breathing is difficult, give oxygen and call physician. |
| Eye Contact: | Flush with water for at least 15 minutes. See a physician if irritation develops. |
| Ingestion: | No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care with this SDS. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal. |
| Most Important symptoms and effects, acute and delayed: | May cause skin or eye irritation upon contact. Avoid breathing vapors. |
| Indication of immediate medical attention and special treatment, if applicable: | Not Available |
| Skin Contact: | Wash with soap and water at first opportunity. Remove contaminated clothing and shoes. Wash or clean clothing before reuse. |

Section 5: Fire-Fighting Measures

| | |
|---|--|
| Suitable extinguishing media: | Use alcohol resistant foam, CO ₂ , dry chemical or water spray when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire. Do not direct a water stream directly into the hot burning liquid. |
| Unsuitable extinguishing media: | N/A |
| Special hazards arising from the chemical: | Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Containers may explode in heat of fire. |
| Precautions for fire-fighters: | Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. |
| Hazardous Combustion Products: | Carbon dioxide, Carbon monoxide, Hydrogen cyanide, Nitrogen containing gases, Hydrocarbons, Toxic fumes, Toxic gases, Isocyanates, Isocyanic Acid |

Section 6: Accidental Release Measures

| | |
|--|---|
| Personal precautions, protective equipment, and emergency procedures: | Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including the material spilled, the quantity of the spill and the area in which the spill occurred. Also, consider the expertise of associates in the area near the spill. Never exceed any occupational exposure limits. |
| Methods and material for containment and cleanup: | Remove or extinguish ignition or combustion sources. Do not allow smoking in the area. Contain spill. Dike with suitable absorbent material. Waste material should be gathered and stored in sealed containers and disposed of under conditions which meet federal, state, and local environmental regulations. Wash area with detergent and water. |

Dalton, GA

Hickory, NC

Mount Airy, NC

Salt Lake City, UT

Section 7: Handling and Storage

| | |
|--|--|
| Precautions for safe handling: | Toxic or severely irritating material. Avoid contacting and breathing the material. Use only in a well-ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes or on skin or clothing. Ground and bond containers when transferring material. Containers with product residue can be dangerous. |
| Conditions for safe storage, including any incompatibilities: | Store in a cool, dry place. Keep tightly sealed. Keep away from sources of ignition. |
| Materials to avoid: | Oxidizing agents, Metals, Acids, Amines, Caustics (bases, alkalis), Water, Alcohols |

Section 8: Exposure Controls and PPE

Exposure Limits

| Component: | OSHA PEL | ACGIH TLV-TWA | ACGIH STEL |
|--|--|--|------------|
| Stoddard solvent | 500 ppm TWA; 2900 mg/m ³ TWA | 100 ppm TWA; 572 mg/m ³ TWA | |
| Titanium dioxide | 15 mg/m ³ TWA (total dust) | 10 mg/m ³ TWA | |
| Quartz (Silica-Crystalline) | see Table Z-3 | 0.05 mg/m ³ TWA (respirable fraction) | |
| Fumed Silica (Particles not otherwise regulated) | 50 mppcf (15mg/m ³) TWA Total Dust; 15 mppcf (5mg/m ³) TWA Respirable fraction | | |
| Toluene diisocyanate | | 0.005 ppm TWA | 0.02 ppm |

Exposure Controls

| | |
|--|---|
| Engineering Measures: | Use local exhaust ventilation or other engineering controls to minimize exposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. |
| Respiratory Protection: | General or local exhaust ventilation is the preferred means of protection. In cases where ventilation is inadequate, respiratory protection may be required to avoid overexposure. Follow respirator manufacturer's directions for use. |
| Hand, eye, skin, body protection: | Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Eye wash system and showers should be available. Avoid all skin contact. Where use can result in skin contact, practice good personal hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking and when leaving work. Wear clothing suitable to prevent skin contact. |

Dalton, GA

Hickory, NC

Mount Airy, NC

Salt Lake City, UT

Section 9: Physical and Chemical Properties

Basic chemical and physical properties

| | | | |
|--|-------------------------------------|--|------------------------|
| Appearance: | Liquid | Density: | 10.79 – 10.99 lbs/gal |
| Color: | Tan | Upper/lower flammability or explosive limits: | 10.7/0.8 |
| Odor: | Hydrocarbon | Vapor pressure: | 68 F (0.52 mm Hg) |
| Odor Threshold: | No data available | Vapor density: | 7.00 (air = 1) |
| pH: | No data available | Relative density: | 2.400 |
| Melting Point/Freezing Point (°F/°C): | No data available/no data available | Solubility(ies): | Reacts slowly in water |
| Viscosity: | 105 - 120 KU | Partition coefficient (n-octanol/water): | No data available |
| Boiling pt/boiling range: | 350.0 -456.0 | Volatiles, % by Volume (calc): | 25.37 |
| Flash point: | 108°F / 42°C | Volatiles, % by Weight (calc): | 16.47 |
| Evaporation rate: | 0.05 | Solubility(ies): | Reacts slowly in water |
| Auto-ignition Temperature: | No data available | Volatile Organic Chemicals (g/L) | |
| Decomposition Temperature: | No data available | (Regulatory, Calculated) | 214.89 |
| Flammability (solid/gas): | N/A | (Actual, Calculated) | 214.86 |

Section 10: Stability and Reactivity

| | |
|--|--|
| Chemical stability: | Stable under normal conditions. |
| Possibility of hazardous reactions: | N/A |
| Conditions to avoid: | Temperatures above flash point in combination with ignition sources. Contamination. Elevated temperatures. Contact with water. |
| Incompatible materials: | Oxidizing agents, Metals, Acids, Amines, Caustics (bases, alkalis), Water, Alcohols. |
| Hazardous decomposition products: | Carbon dioxide, carbon monoxide, Hydrogen cyanide, Nitrogen containing gases, Hydrocarbons. Toxic fumes, Toxic gases, Hydrogen chloride. |

Section 11: Toxicological Information

Routes of Exposure: Eye contact
Inhalation
Skin contact
Ingestion

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.

Inhalation Toxicity Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea.

Skin Contact Can cause moderate skin irritation. May cause allergic skin reaction.

Eye Contact Causes eye irritation.

Ingestion Toxicity Harmful if swallowed. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.



SAFETY DATA SHEET According to GHS

PO Box 1528 • Mount Airy, NC 27030-1528
800.346.8229 • Fax 336.789.9586 • www.NCFI.com

Dalton, GA

Hickory, NC

Mount Airy, NC

Salt Lake City, UT

Long-Term (Chronic) Health Effects

Carcinogenicity Contains Titanium Dioxide which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence with respect to humans and sufficient evidence in experimental animals.

Cancer hazard: Contains Crystalline Silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust generated from sanding surfaces or spray mists.

Possible cancer hazard: contains toluene diisocyanate which may cause cancer. Risk of cancer depends on duration and level of exposure to dust generated from sanding surfaces or spray mists.

Inhalation

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intention misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Overexposure may cause lung damage.

Skin Contact

Prolonged contact may cause an allergic skin reaction.

Product Toxicology Data

Oral Acute Toxicity Estimate (ATE) 2,651.48 mg/kg

Dermal Acute Toxicity Estimate (ATE) 56,811.21 mg/kg

Component Toxicology Data:

| Chemical Component | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--|------------------------------|-----------------------------------|---------------------------------------|
| 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 1,3-diisocyanatomethylbenzene and alpha.-hydro-omega-hydroxypoly [oxy(methyl-1,2- ethanediyl)] | Oral LD50 Rat > 5000 mg/kg | Dermal LD50 Rabbit > 5000 mg/kg | Inhalation LC50 (4h) Rat > 20.00 mg/L |
| Stoddard solvent | Oral LD50 Rat > 5 g/kg | | Inhalation LC50 Rat > 6.10 mg/L |
| Titanium dioxide | Oral LD50 Rat > 25,000 mg/kg | Dermal LD50 Rabbit > 10,000 mg/kg | Inhalation LC50 (4h) Rat > 6.82 mg/L |
| Quartz | Oral LD50 Rat > 22,500 mg/kg | Dermal LD50 Rabbit > 2000 mg/kg | Inhalation LC50 (4h) Rat > 20.00 mg/L |
| Butyl carbitol acetate | Oral LD50 Rat 6500 mg/kg | Dermal LD50 Rabbit 14,500 mg/kg | Inhalation LC50 (4h) Rat 72.50 mg/L |
| Fumed silica | Oral LD50 Rat > 1000 mg/kg | | |
| (d)-Limonene | Oral LD50 Rat > 5000 mg/kg | Dermal LD50 Rabbit > 5000 mg/kg | |
| Toluene diisocyanate | Oral LD50 Rat 6170 mg/kg | Dermal LD50 Rabbit > 16,000 mg/kg | Inhalation LC50 (4h) Rat 0.10 mg/L |
| Carcinogens: | | | |
| Titanium dioxide | | | IARC: 2B NTP: 1 OSHA: |
| Quartz | | | IARC: 1 NTP: 2 OSHA: |
| Toluene diisocyanate | | | IARC: 2B |

Section 12: Ecological Information

| | |
|---------------------------------------|-------------------|
| Ecotoxicity: | No data available |
| Persistence and degradability: | No data available |
| Bioaccumulative potential: | No data available |

Toxicity data, if available, are listed in Section 11.

Dalton, GA

Hickory, NC

Mount Airy, NC

Salt Lake City, UT

Section 13: Disposal

| | |
|------------------------|---|
| Waste disposal: | Refer to other sections of this SDS to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations. |
|------------------------|---|

Section 14: Transport

| | |
|--------------------------------------|--|
| UN number: | UN1263 |
| UN Proper shipping name: | Paint |
| Transport Hazard class(es): | 3 |
| Packing group, if applicable: | III |
| Other: | Not regulated for non-bulk domestic ground shipments for packaging of 450 liters (119 gallons) or less (DOT 49CFR 173.150(f)). |
| Marine Pollutant: | No |

Section 15: Regulatory

| | | | |
|-------------------------------------|---|--------------|--------------|
| Inventory Status: | All components TSCA listed | | |
| US Federal Regulations: | | CAS # | % |
| SARA EHS Chemicals | Toluene Diisocyanate | 26471-62-5 | 0.1 - 1 |
| CERLA | Toluene Diisocyanate | 26471-62-5 | 0.1 - 1 |
| SARA 313 | 2-(2-Butoxyethoxy)ethyl acetate | 124-17-4 | 3 - 7 |
| | Toluene diisocyanate (mixed isomers) | 26471-62-5 | 0.1 - 1 |
| SARA 311/312 | Health (Acute): Y Health (chronic): Y Fire (Flammable): Y Pressure: N Reactivity: Y | | |
| US State Regulations: | | | |
| California Prop 65 Chemicals | Cancer | CAS # | % |
| | Titanium dioxide | 13463-67-7 | 3 - 7 |
| | Crystalline Silica | 14808-60-7 | 3 - 7 |
| | Toluene Diisocyanate | 26471-62-5 | 0.1 - 1 |
| | Carbon Black | 1333-86-4 | 0.01 - 0.1 |
| | Cumene | 98-82-8 | 0.01 - 0.1 |
| | Benzene | 71-43-2 | 0.001 - 0.01 |
| | Arsenic | 7440-38-2 | <10 ppb |
| | Lead | 7439-92-1 | <10 ppb |
| | Nickel | 7440-02-0 | <10 ppb |

| | | | |
|--|---------------------|-----------|---------------|
| | Reproductive | | |
| | Methyl Alcohol | 67-56-1 | 0.001 - 0.010 |
| | Benzene | 71-43-2 | 0.001 - 0.01 |
| | Lead | 7439-92-1 | <10 ppb |

Canadian Regulations:

CEPA DSL: The components of this product are listed on the Canadian Domestic Substances List.
WHMIS Hazard Class: B3 D2A



SAFETY DATA SHEET According to GHS

PO Box 1528 • Mount Airy, NC 27030-1528
800.346.8229 • Fax 336.789.9586 • www.NCFI.com

Dalton, GA

Hickory, NC

Mount Airy, NC

Salt Lake City, UT

Section 16: Other

| | |
|-------------------------------|-----------|
| MSDS Preparation Date: | 09/4/2015 |
| Revision Date: | |

IMPORTANT NOTICES

This notification is a part of the Safety Data Sheet document and must not be detached. Any copying and redistribution of the Safety Data Sheet shall include copying of this notice and attaching the copy to the redistributed Safety Data Sheet copies.

This information is furnished without warranty, expressed, or implied, except that it is accurate to the best knowledge of NCFI. The data on this sheet relates only to the specific material designated herein. NCFI assumes no legal responsibility for use or reliance upon these data.