


# Designed With Ease of Service in Mind

Gusmer H-20/35 system features easy access and service to the electrical cabinet. With standard off-the-shelf hardware it's an easy-to-use and easy-to-maintain design.













**Commercial Wall** 

**Concrete Lifting** 

**Residential Insulation** 

**Rim and Band Joist** 

**Roof Insulation** 



# Understand Spray Performance

Use this chart to help identify how the system will work most efficiently with each mix chamber.

Flow rates are based on a material viscosity of 60 cps. *See example below*.

#### How to use this chart

Select spray pressure


Select mix chamber or flow rate

#### **Spray Foam Example**


Mix chamber: AR6060 (03)

Pressure: 1250 psi Flow rate: 22 lb/min\*

\*Output of flat tip will be slightly less than round equivalent



# Simple Controls for Ease of Use



## **Gusmer H-20/35**

## Over 35% fewer connection points than comparable non-Graco systems

- Point-to-point wiring
- Easy troubleshooting

## Circulation Valves

- Proven design
- Easy pressure balancing
- Set up for easy recirculation

#### Easy Troubleshooting Diagnosis

• Y-strainers for analog inlet temp and pressure gauges

#### Graco Horizontal Pump Line

- Robust, industry proven
- Slower cycle rate
- Longer pump life
- Easy maintenance

### Clear Pump Cover

• For easy visual movement of pump line



#### Electrical Cabinet

- Easy access
- Simple controls

#### **Reversing Sensor**

Non-contact for longer life

### **Hybrid Heaters**

- Proven design
- Quick, even heating

#### **Pump Lowers**

- Easy to service
- Multiple sizes for off-ratio applications

#### Hydraulic System

- Actively cooled system to keep hydraulic fluid cool
  - 3.5 gal hydraulic fluid reservoir

#### Caster Kit

• Kit part #17G340 for portability



# Tech Specs and Ordering Information



GUSMER MODEL	GH-2	GH-4
Maximum Working Pressure	2000 psi (138 bar, 13.8 MPa)	2000 psi (138 bar, 13.8 MPa)
Maximum Hose Length	320 ft (97.5 m)	420 ft (128 m)
Maximum Fluid Temperaure	190°F (88°C)	190°F (88°C)
Output	28 lbs/min (12.3 kg/min)	45 lbs/min (20.4 kg/min)
Weight	585 lbs (265kg)	585 lbs (265kg)
Dimensions (W x D x H)	32 in x 21 in x 54 in (81 cm x 53 cm x 137 cm)	32 in x 21 in x 54 in (81 cm x 53 cm x 137 cm)
Operation and Repair Manual	3A5376	3A5376

#### Bare Packages

**26C200** GH-2 Base, 10kW, 230V, 1-ph
 **26C699** GH-4 Base, 15kW, 230V, 3-ph

 **26C201** GH-2 Base, 10kW, 230V, 3-ph
 **26C700** GH-4 Base, 15kW, 400V, 3-ph

 **26C202** GH-2 Base, 10kW, 400V, 3-ph

### **Basic Packages**

Includes system, gun, 10 ft whip hose and one 50 ft hose section

APC200	Fusion AP package, GH-2 Base 10kW, 230V, 1-ph
APC201	Fusion AP package, GH-2 Base 10kW, 230V, 3-ph
APC202	Fusion AP package, GH-2 Base 10kW, 400V, 3-ph
CSC200	Fusion CS package, GH-2 Base 10kW, 230V, 1-ph
CSC201	Fusion CS package, GH-2 Base 10kW, 230V, 3-ph
CSC202	Fusion CS package, GH-2 Base 10kW, 400V, 3-ph
P2C200	Probler P2 package, GH-2 Base 10kW, 230V, 1-ph
P2C201	Probler P2 package, GH-2 Base 10kW, 230V, 3-ph
P2C202	Probler P2 package, GH-2 Base 10kW, 400V, 3-ph
APC699	Fusion AP package, GH-4 Base 15kW, 230V, 3-ph
P2C699	Probler P2 package, GH-4 Base 15kW, 230V, 3-ph
APC700	Fusion AP package, GH-4 Base 15kW, 400V, 3-ph
P2C700	Probler P2 package, GH-4 Base 15kW, 400V, 3-ph

### **Additional Hose Packages**

Includes system, gun, 10 ft whip hose and five 50 ft hose sections

AHC200 AHC201	Fusion AP package, GH-2 Base 10kW, 230V, 1-ph Fusion AP package, GH-2 Base 10kW, 230V, 3-ph
AHC202	Fusion AP package, GH-2 Base 10kW, 400V, 3-ph
CHC200	Fusion CS package, GH-2 Base 10kW, 230V, 1-ph
CHC201	Fusion CS package, GH-2 Base 10kW, 230V, 3-ph
CHC202	Fusion CS package, GH-2 Base 10kW, 400V, 3-ph
PHC200	Probler P2 package, GH-2 Base 10kW, 230V, 1-ph
PHC201	Probler P2 package, GH-2 Base 10kW, 230V, 3-ph
PHC202	Probler P2 package, GH-2 Base 10kW, 400V, 3-ph

Includes system, gun, 10 ft whip hose and **six** 50 ft hose sections

AHC699	Fusion AP package, GH-4 Base 15kW, 230V, 3-ph
PHC699	Probler P2 package, GH-4 Base 15kW, 230V, 3-ph
AHC700	Fusion AP package, GH-4 Base 15kW, 400V, 3-ph
PHC700	Probler P2 package, GH-4 Base 15kW, 400V, 3-ph



### **GRACO HEADQUARTERS**

#### **WORLDWIDE HEADQUARTERS**

**Graco Inc.** 88-11th Avenue N.E. Minneapolis, MN 55413 Tel: 612-623-6000

# **Graco Has You Covered**

Facilities Worldwide for Global Support



#### **Quality First**

At Graco we pride ourselves on providing best-in-class products. Engineered solutions are manufactured in our own facilities, with the highest standards in the industry. We provide you with world-class customer support and expertise to help solve your application challenges.



#### **Global Reach**

Graco has facilities across the globe to provide you with the products and service you need, where you live. Plus, Graco has dedicated field experts in all areas of the world to support the products we sell.



#### **Product Capabilities**

Graco has a broad range of products that are engineered and tested to perform in the harshest environments so you can be certain your equipment is protected and working at peak performance.

### Contact us today!

