



NCFI Polyurethanes
 Div. of Barnhardt Manufacturing Co.
 PO Box 1528 • Mount Airy, NC 27030
 800-346-8229 www.NCFI.com

Technical Data Sheet

EnduraTech™ AP (70-016)
ACRYLIC PRIMER

DESCRIPTION:

Enduratech AP (70-016) is a low solids 100% acrylic base primer designed to properly condition a variety of substrates prior to application of spray polyurethane foam (SPF) or acrylic coatings. It is available in clear, gray, or black.

DISTINGUISHING CHARACTERISTICS:

- Increases yield of topcoats
- Reduces temperature shock of SPF applied on cool days
- Improves foam and coating adhesion
- Water-based
- Seals and conditions

TYPICAL PHYSICAL PROPERTIES:

<u>Properties</u>	<u>Typical Values</u>
Solids by Volume	15%
Weight per Gallon	8.0 lbs.
Viscosity	500-800 cps
Clean-up	Water
Re-coat Time	4-8 hours

INSTALLATION:

- May be applied by spray or heavy nap roller. However, airless spray is recommended for consistency.
- All surfaces must be clean, dry, and free of dirt, grease, oil, and other contaminants that would interfere with proper adhesion.
- Apply at the rate of at least ¼ gallon per 100 square feet.
- Apply at temperatures above 50°F.
- Apply only when Weather conditions will permit coating to dry before rain, dew, or freezing temperatures occur.
- For details, see Coating Specification Guide.

The information on our data sheets is to assist customers in determining whether our products are suitable for their applications. The customers must satisfy themselves as to the suitability for specific cases. NCFI Polyurethanes warrants only that the material shall meet its specifications; this warranty is in lieu of all other written or unwritten, expressed or implied warranties and NCFI Polyurethanes expressly disclaims any warranty of merchantability, fitness for a particular purpose, or freedom from patent infringement. Accordingly, buyer assumes all risks whatsoever as to the use of the material. Buyer's exclusive remedy as to any breach of warranty, negligence or other claim shall be limited to the purchase price of the material. Failure to adhere strictly to recommended procedures shall relieve NCFI Polyurethanes of all liability with respect to the material or the use thereof.