

EnduraTechTMSP (70-018)

SUPER PUTTY

DESCRIPTION:

Enduratech SP is a premium quality elastomeric patching compound, which combines 100% acrylic polymers with a hi-solids content.

INSTALLATION:

- Thoroughly clean off all dirt and debris
- Apply only when not subjected to rain
- Enduratech SP needs 24 hours of sunshine to dry
- Do not apply when roof temperature is less than 50°F or when wet
- Millage can affect cure time
- Acrylic-based products must cure before being subjected to freezing or moisture. Example of ideal conditions: 4-6 hours above 70°F and low humidity
- For application details see specific Guide Specifications

TYPICAL PHYSICAL PROPERTIES:

Properties	Typical Values
Type of Resin	100% Acrylic
Color	White
Shelf Life	One(1) Year
Solids Content	60%
Elongation	Excellent
Adhesion	Excellent
UV Reflectance	Good

AVAILABILITY AND COST:

Enduratech SP may be purchased directly from NCFI Polyurethanes (800-346-8229).

WARRANTY:

No specific warranties implied. It is the responsibility of the Tier One contractor to ensure that all products are used in the accordance with federal, state, and city codes. This includes but is not limited to building and fire codes.

MAINTENANCE:

Periodic maintenance of Enduratech Premier Roofing System coatings and roofing systems ensures extended performance and reduces life cycle costs.

The information on our data sheets is to assist customers in determining whether our products are suitable for their applications. The customers must satisfy themselves as to the suitability for specific cases. NCFI Polyurethanes warrants only that the material shall meet its specifications; this warranty is in lieu of all other written or unwritten, expressed or implied warranties and NCFI Polyurethanes expressly disclaims any warranty of merchantability, fitness for a particular purpose, or freedom from patent infringement. Accordingly, buyer assumes all risks whatsoever as to the use of the material. Buyer's exclusive remedy as to any breach of warranty, negligence or other claim shall be limited to the purchase price of the material. Failure to adhere strictly to any recommended procedures shall relieve NCFI Polyurethanes of all liability with respect to the material or the use thereof.

