



## InsulStar® SmartSPF (11-036) Insulation Certification

Closed Cell Spray-in-Place Polyurethane Foam Insulation System

Date Installation completed: \_\_\_\_\_

Application Contractor \_\_\_\_\_  
(Company Name)

Address \_\_\_\_\_

City/State/Zip \_\_\_\_\_ Phone # \_\_\_\_\_

Building Address - Street \_\_\_\_\_

City/State/Zip \_\_\_\_\_

**Indicate areas insulated -**

Exterior Stud Wall: Average thickness \_\_\_\_\_ R-Value \_\_\_\_\_

Ceiling insulation: Average thickness \_\_\_\_\_ R-Value \_\_\_\_\_

Roof Deck insulation: Average thickness \_\_\_\_\_ R-Value \_\_\_\_\_

Crawl Space/Basement: Average thickness \_\_\_\_\_ R-Value \_\_\_\_\_

Special Areas insulated: \_\_\_\_\_

I (print name) \_\_\_\_\_ as an Independent contractor, certify that the InsulStar® Smart 11-036 Insulation installed on this project was applied in accordance with the NCFI recommendations and specifications as stated on the product data sheet and the InsulStar Application Specifications in the amount as indicated on this certification.

\_\_\_\_\_ (signed) Date \_\_\_\_\_

### InsulStar® Smart 11-036 Spray Polyurethane Foam Insulation System R-Value Chart

Thickness	R-Value		Thickness	R-Value
1"	7.1		5.5	37
2"	14		6"	40
3"	20		7"	47
3.5"	23		8"	53
4.5"	30		9"	60

